

Appln. No. 10/623,253
Amendment dated June 5, 2006
Reply to Office Action of March 13, 2005

Amendments to the Claims:

Please amend claims 1 and 2 as follows. The following listing of claims will replace all prior versions, and listings, of claims in the application.

Listing of Claims:

Claim 1 (Currently Amended). A molded product of a weather strip for an automobile ~~formed by~~ comprising placing an insert in a molding space formed by an upper die and a lower die, followed by [[an]] injection ~~process of~~ molding material to form a molded
5 body, wherein,

said insert comprises an insert body embedded in the molded body and a removing part which is integrally formed with the insert body and coupled to the insert body via a thin part at a first end while a second end is projected to expose at a
10 non-front surface side;

the removing part functions to prevent the insert body from moving as the second end is firmly held between the upper die and the lower die during a molding operation and said thin part is embedded in the molded body;

Appln. No. 10/623,253
Amendment dated June 5, 2006
Reply to Office Action of March 13, 2005

15 the removing part is removed from the insert body by cutting the thin part after being released from the die mold;

and a groove is formed at the position where the removing part existed and is present at a non-front side surface which is not seen from outside.

Claim 2 (Currently Amended). A molded product of a weather strip for an automobile ~~formed by~~ comprising placing an insert in a molding space formed by an upper die and a lower die, followed by [[an]] injection ~~process of~~ molding material to form a molded
5 body, wherein,

the insert comprises an insert body embedded in the molded body and a removing part which is integrally formed with the insert body and coupled to the insert body via a cutting line or cutting ditch at a first end while a second end is projected to
10 expose at a non-front surface side;

the removing part functions to prevent the insert body from moving as the second end is firmly held between the upper die and the lower die during a molding operation and said cutting line or cutting ditch is embedded in the molded body;

Appln. No. 10/623,253
Amendment dated June 5, 2006
Reply to Office Action of March 13, 2005

15 the removing part is removed from the insert body by cutting
the cutting line or the cutting ditch after being released from
the die mold;

 and a groove is formed at the position where the removing
part existed and is present at a non-front side surface which is
20 not seen from outside.